



Simma Software

VNA-BT

J1939 to Bluetooth

Overview

The VNA-BT, with Binary Boost™, is a high-performance low latency vehicle network adapter. It allows any host device with a Bluetooth connection to simultaneously communicate on all three vehicle networks.

The VNA-BT supports dual J1939/CAN interfaces, with auto baud detection, and a single J1587/J1708 interface. All interfaces are certified for zero packet loss with continuous 100% bus load.

Power Savings

All VNA devices (VNA-BT, VNA-WiFi, VNA-USB, and VNA-SA) avoid vehicle battery drain by automatically entering deep sleep mode when idle.

Binary Boost™

Binary Boost™ is a simple and efficient technology for doubling the bandwidth between the host and VNA-BT.

Features

- J1587/J1708 x1, with 5.2.2.1 compliance
- J1939/CAN x2, with auto baud (250K and 500K)
- Wireless Bluetooth 2.1 interface up to 3Mbps
- Internal message buffering
- 200 message filters or pass-all mode
- Collision detection, with automatic retries
- Field programmable
- SAE J1939-82 certified
- Automatic deep sleep mode (< 1mA)
- Load dump and reverse bias protection



Simma Software, Inc. specializes in real-time embedded software for the automotive industry. Products and services include protocol stacks, bootloaders, device drivers, training, and consultation on the following technologies: J1939, CAN, J1587, J1708, J2497, J1922, J1850, J1979, ISO 15765, OBD-II, CANopen.

Simma Software, Inc
5940 South Ernest Drive
Terre Haute, IN 47802
Toll Free: 888-256-3828
Fax: 208-445-2913
www.simmasoftware.com